

L'Olio 100%

Solvent free mono coat hardwax oil for wooden floors

L'Olio 100% is a ready to use high solid blend of natural and hard wax oils that colours and finishes your indoor wood surfaces in one single coat. Perfect for finishing high traffic floors, stairs, table and counter tops, furniture and wood millwork. It is suitable for application on site or industrially. It is solvent free, easy to apply and gives a warm and rich effect to the wood in a single coat. It does not contain drying compounds based of lead or cobalt for a major safety; the product has good drying time and guarantees high protection against water and standard household products. Available neutral and in 30 intermixible colours.

Technical data at 20°C – 60% R.U.

Aspect	Liquid
Density	0,950 – 0,990 kg/l
Viscosity	60 – 70" Ford n° 4
Spreading	Within 15 – 20 minutes
Touch dry	6 – 8 hours
Polishing	24 hours
Yield	35 – 40 m ² /litre
Application temperature	> 10 °C
Storage	12 months in original packing at T >10 °C
VOC content	35 g/l
Tool cleaning	Immediately after use with Diluente RMD/91 or Green Cleaner
Available packaging	25ml, 100ml, 1L & 2,5L for the neutral 100ml, 1L for the coloured version

Application Instructions

Tables/Countertops/Furniture

1. Sand the wood in proper progression (60-80-100/120) with the last grit to be used for final sanding of 100-120 (sanding too fine will prevent the oil from absorbing into the wood completely)
2. Clean the surface with a brush, vacuum or a slightly damped tack cloth to remove any remaining sanding dust. The wood surface can then be "water-popped" too open the grain up and allow for deeper colour and oil penetration. Allow the wood to dry completely.
3. Mix the L'Olio 100% before use adding the Oil Linker at 10%. Colour and drying time remain unchanged. The mix has a pot life of about 8 hours.
4. Apply a small quantity of L'Olio100% spreading it with flexible trowel, spatula or with white, red or beige buffing pad to spread it evenly.
5. A final buffing/wiping of the entire surface with new white buffing pad or cotton cloth, leaving a non-sticky surface with no oil film. See drying times above.



Varnishes & Finishing

L'Olio 100%



Certifications



TOVER[®]

Made in Italy



Tover S.r.l.
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax.+39/011.7792749
www.tover.com - info@tover.com

Maintenance

Immediately after the application it is possible to apply the water-proofing agent I.R.O to improve water resistance if desired.

We recommend to wait at least 20 days after the application before doing any wet cleaning or maintenance. Simply vacuum or dry dust mop.

For the cleaning of floors treated with L'Olio 100% we suggest to use our Deteroil coconut soap. To revive the surface periodically Tover Lux liquid wax in water emulsion can be applied by damp mop to rejuvenate the floor. Lux is available in semi-glossy, matte and white. As an alternative you can use I.R.O.

Repair

To repair scratches and small worn areas use the same oil used for the finishing. Wash the floor with Deteroil. Slightly sand the area to be repaired with the same abrasive paper and apply a very thin coat of oil with a cloth. The same sanding grit (and water popping) as originally used will uniformly blend the coloured oils. Wipe the oil dry as above.

Notes

Do not apply L'Olio 100% on previous lacquers, nitro sealers or any other sealing treatment.

DO NOT EXCEED the recommended quantity, as the finish would be weaker and sticky.

Woods containing oils like teak, iroko or olive tree, resinous woods could significantly slow down the drying, even of several days. Also high humidity content, low temperatures are factors of drying slowing down.

When you use the coloured version, always proceed to make a test on a small area to evaluate the final effect.

Safety norms

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the label and consult the safety data sheet before using the product.

Cloths and sponges soaked of product might catch fire through self-combustion. After use, wet them with a lot of water, let them dry and dispose them in accordance with local in force regulations.

Waste disposal

Dispose the unused product and empty containers in accordance with local regulations.



Varnishes &
Finishing

L'Olio 100%



Certifications



The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated. Rev 06 from 15-01-2019. Current Technical Data Sheet replaces the previous one

TOVER[®]



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax. +39/011.7792749
www.tover.com - info@tover.com